

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 April 2004 (22.04.2004)


PCT

(10) International Publication Number  
**WO 2004/033336 A1**

- (51) International Patent Classification<sup>7</sup>: **B65D 51/28**, 41/50, 51/22
- (21) International Application Number: PCT/AU2003/001339
- (22) International Filing Date: 10 October 2003 (10.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2002951977 10 October 2002 (10.10.2002) AU
- (71) Applicants (*for all designated States except US*): **LEO ENGINEERING PTY LTD** [AU/AU]; 44 Parraweena Road, Taren Point, New South Wales 2229 (AU). **WELLINGTON INDUSTRIES PTY LTD** [AU/AU]; 44 Parraweena Road, Taren Point, New South Wales 2229 (AU).
- (72) Inventors; and  
(75) Inventors/Applicants (*for US only*): **NEUMEYER, Mark, Damian** [AU/AU]; c/- 44 Parraweena Road, Taren Point, New South Wales 2229 (AU). **NEUMEYER, Leo** [AU/AU]; c/- 44 Parraweena Road, TAREN POINT, New South Wales 2229 (AU). **WELLINGTON, Kevin** [AU/AU]; c/- 44 Parraweena Road, Taren Point, New South Wales 2229 (AU).
- (74) Agent: **GRIFFITH HACK**; GPO Box 4164, SYDNEY, New South Wales 2001 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: IMPROVEMENTS TO TWO-PART VESSELS



(57) Abstract: A device (10) for location at an opening to a receptacle comprises a projection in the form of a hingedly moveable cutter (32) which is located on a sleeve (38) which is adapted for location at the opening of the receptacle. The device (10) also comprises a lid (12) for location at the opening including a sealed compartment (20) in the lid (12) that is positionable at the opening and a longitudinal rib (24) located inside the lid (12). In use when the lid (12) and its compartment (20) is positioned at the opening and the lid is rotated relative to the receptacle, the rib (24) is caused to act on the cutter (32) to move it into a position whereby it opens the sealed compartment (20). The movement of the lid (12) in a unidirectional rotation alone with respect to the receptacle causes both opening of the compartment (20) followed by removal of the lid (12) from the receptacle.

WO 2004/033336 A1



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

- 1 -

**IMPROVEMENTS TO TWO-PART VESSELS****Field of the Invention**

The present invention relates to vessels having two  
5 compartments. Such vessels can be used in all manner of  
domestic, medical and industrial applications where the  
initiation of mixing of two substances needs to be  
controlled, and will primarily be described with reference  
to this context.

10

**Background Art**

Many different types of containers are known in the  
prior art which enable the separation of two components of  
a mixture until use of the mixture is required. In  
15 containers where two or more products are supplied pre-  
mixed, the potency of the mixture may reduce rapidly with  
time. For example, mixtures such as medicines and  
antidotes have a limited shelf life after the active  
ingredients are mixed.

20

Some of the prior art containers have a membrane  
fitted into the interior of a lid of the container, the  
membrane made of tinfoil or thin plastic for example, which  
can be perforated by application of external pressure to an  
upper surface of the lid in order to actuate movement of a  
25 depressible tab or knife edge located in the lid. These  
containers are generally of complex construction which can  
make them costly to manufacture.

Generally in order to safely access the contents of  
the known prior art vessels, a multiple-step opening  
30 procedure must be followed. In each of US 6,138,821 (Hsu)  
and DE19950884 (Wella AG), a prior art container is shown  
in which the lid of the container has a compartment which  
is opened by moving the lid so that a fixed projection  
opens the compartment therein. In the case of US 6,138,821  
35 (Hsu), once the compartment in the lid has been opened, and  
the lid is removed, the sharp projection fitted to the

- 2 -

bottle throat needs to be removed by hand so that the contents can then be consumed without any risk of injury to the lips of a user. This introduces the possibility of injury to the fingers of a user, or contamination of the contents of the vessel by touching the throat region with dirty fingers. In DE19950884 (Wella AG), the actuation of the compartment opening mechanism by rotation of the cap downward in one direction causes the sharp projection to fall into the bottle itself and presents an even greater hazard to users if oral consumption by humans from such a bottle occurs. To access the bottle mouth for rapid pouring out of the contents, the cap then needs to be rotated in a reverse direction. Such a device is unsuitable for dispensing a tablet from the cap, and small fragments of foil may dislodge and fall into the bottle.

#### Summary of the Invention

In a first aspect the present invention provides a device for location at an opening to a receptacle comprising:

- a projection adapted for association with the receptacle at the opening;
  - a lid for location at the opening including a compartment that is positionable at the opening when the lid is located thereat; and
  - engagement means associated with the lid;
- wherein when the compartment is positioned at or near the opening and the lid is moved in a given direction relative to the receptacle, the engagement means is caused to act on the projection such that the projection itself is moved into a position whereby it opens the compartment.

By associating the projection with the receptacle, and by causing the projection itself to be moved, the lid including the compartment can be of simpler construction

- 3 -

than those known in the art for this purpose, and, as a consequence, simpler to use.

Preferably the projection is hingedly moveable into a position to open the compartment.

5        Preferably the compartment is closeable in use with an openable seal. More preferably the projection least partially detaches the seal from the compartment. Most preferably the projection includes a cutter portion adapted for cutting the seal.

10       Preferably the engagement means is a protrusion located internally of the lid and externally of the compartment. More preferably the protrusion comprises at least one flange located on an external wall of the compartment and arranged to bias the projection into a  
15       location that opens the compartment as the lid is moved in the given direction.

Preferably the lid is rotatable relative to the receptacle. More preferably the lid is attached to the receptacle via rotation in a first direction and is  
20       detached via rotation in a second opposite direction, the second direction corresponding to said given direction.

Preferably the lid is adapted for threadable engagement with the receptacle.

Preferably the compartment is also adapted for access  
25       from another location other than via the seal. More preferably the access adaptation is a closeable orifice in an exterior surface of the lid. Most preferably a removeable or insertable disc is arrangeable for engagement with a rim of the orifice in a closed position.  
30       Alternatively the access adaptation is a closeable projecting teat located at an exterior surface of the lid.

Preferably the projection is integral with the receptacle at the opening or part of an insert locatable in the receptacle opening. More preferably the insert is a  
35       sleeve positionable in a neck of the receptacle and the projection protrudes inwardly of the sleeve.

- 4 -

Most preferably the sleeve comprises:

- a mounting for holding the sleeve in a freely rotatable but axially fixed manner in relation to the lid;
- 5       - one or more deformable retaining means located externally of the sleeve for holding it in an associative frictional engagement at the opening of the receptacle;
- 10       - a rib flange located at an internal wall of the sleeve and arranged to abut the engagement means upon rotatable movement of the lid at the receptacle,

wherein when the lid is rotated the engagement means abuts the rib flange and further rotation of the lid thus causes the lid and the sleeve to rotate together but only as allowed by the deformation of the retaining means, thereby detaching the sleeve from its association with the receptacle.

The operation of this apparatus in use means that no separate intervention by a user needs to occur to remove the projection from its association with the opening of the receptacle prior to consuming the receptacle contents.

Preferably the mounting comprises a circumferential or part-circumferential retaining rib located on the internal wall of the sleeve which in use is seated in a groove located on an outer surface of the compartment.

Preferably the lid is provided with a tamper-evident seal. More preferably the seal is a strip detachably positioned at an edge rim of the lid which adjoins the receptacle in use.

In a second aspect the present invention provides a method of opening a compartment located in a lid positionable at a receptacle, including the step of moving the lid in a given direction relative to the receptacle at an opening of the receptacle so that a projection

- 5 -

associated with the receptacle is itself moved into a position to open the compartment.

5 In a third aspect the present invention provides a method of opening a compartment located in a lid positionable at an opening of a receptacle wherein movement of the lid in a unidirectional rotation alone with respect to the receptacle causes compartment opening followed by removal of the lid from the receptacle.

10 As a result, the method of opening the receptacle is simplified in comparison to the known prior art devices so that the user only needs to undertake one intuitive action of turning the lid of the receptacle to accomplish two separate functions immediately prior to use of the combined contents of the compartment and the receptacle.

15 Preferably the opening of the compartment brings it into fluid communication with the receptacle.

Preferably the method of the second and third aspect uses a device as defined in the first aspect.

20 In a fourth aspect the present invention provides a lid for location at an opening as defined in the first aspect.

In a fifth aspect the present invention provides a receptacle being fitted with a device as defined in the first aspect.

25 In a sixth aspect the present invention provides a sleeve which is insertable into an opening of a receptacle and having a projection as defined in the first aspect.

### **Brief Description of the Drawings**

30 Notwithstanding any other forms which may fall within the scope of the present invention, preferred forms of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

35 Figure 1a, 1b and 1c respectively show a side elevation, underside plan elevation and underside perspective view of one embodiment of a lid in accordance

- 6 -

with the invention.

Figure 2 shows a perspective exploded sectional view of the lid of Figure 1 when fitted with an openable seal and a sleeve which is insertable into the opening of a receptacle as shown, the sleeve having a projection in accordance with the invention fitted thereto.

Figures 3a, 3b and 3c each show a perspective view of the sleeve of Figure 2 which is insertable into the opening of a receptacle and having a projection fitted thereto in accordance with the invention, the projection being moveable into various positions as shown in the drawings.

Figures 4a and 4b respectively show a plan and a side sectional view of the sleeve of Figure 2.

Figures 5a, 5b and 5c respectively show a perspective, another perspective and a side view, all views being partially sectioned, of the in use assembly of lid, seal and sleeve of Figure 2, the projection on the sleeve not yet moved from its initial position.

Figures 6a, 6b and 6c respectively show a perspective, another perspective and a side view, all views being partially sectioned, of the in use assembly of lid, seal and sleeve of Figure 2, the projection on the sleeve being partially moved from its initial position into its deployed position to cut the seal.

Figures 7a, 7b and 7c respectively show a perspective, another perspective and a side view, all views being partially sectioned, of the in use assembly of lid, seal and sleeve of Figure 2, the projection on the sleeve being fully moved from its initial position into its deployed position to cut the seal.

Figures 8a and 8b respectively show a perspective, and another perspective view, both views being partially sectioned, of the in use assembly of lid, seal and sleeve of Figure 2, the projection on the sleeve having been rotated with respect to the lid so that the seal is cut open to release the contents of the compartment in use.



- 7 -

Figures 9a and 9b respectively show a perspective, and a side elevational view, both views being sectioned, of the in use assembly of lid, seal and sleeve of Figure 2 when fitted to a receptacle opening, the projection on the sleeve not yet moved from its initial position into its deployed position to cut the seal.

Figure 10 shows a top perspective, exploded, sectional view of a further embodiment of a lid in accordance with the invention, the lid fitted with an openable seal and a sleeve which is insertable into the opening of a receptacle, the sleeve having a projection in accordance with the invention fitted thereto; the lid also having a second openable access orifice.

Figure 11 shows a side elevational view of the embodiment of Figure 10.

Figures 12a and 12b respectively show a perspective, and a side elevational view, both views being sectioned, of the in use assembly of lid, seal and sleeve of Figures 10 and 11 when fitted to a receptacle opening, the projection on the sleeve not yet moved from its initial position into its deployed position to cut the seal.

Figure 13 shows a top perspective, exploded, sectional view of a further embodiment of a lid in accordance with the invention, the lid fitted with an openable seal and a sleeve which is insertable into the opening of a receptacle, the sleeve having a projection in accordance with the invention fitted thereto; the lid also having a second openable access orifice.

Figure 14 shows a side elevational view of the embodiment of Figure 13.

Figures 15a and 15b respectively show a perspective, and a side elevational view, both views being sectioned, of the in use assembly of lid, seal and sleeve of Figures 13 and 14 when fitted to a receptacle opening, the projection on the sleeve not yet moved from its initial position into its deployed position to cut the seal.

- 8 -

Figure 16 shows a perspective view of a further embodiment of a lid in accordance with the invention.

Figure 17 shows a side elevational view of the lid shown in Figure 16.

5        Figure 18 shows a perspective view of one embodiment of a sleeve which is insertable into the opening of a receptacle and having a projection fitted thereto in accordance with the invention.

10       Figure 19 shows a side elevational view of the sleeve shown in Figure 18.

### **Modes for Carrying out the Invention**

Referring to the drawings, a device 10 is shown for location at an opening throat 11 of a receptacle such as a  
15       bottle or other storage container. The device 10 includes a lid 12 for location at the opening throat 11. The lid has a circular top plate 14 and a skirt 16 depending therefrom, the exterior surface of the skirt 16 having longitudinal ribs or grooves 18 to facilitate finger grip  
20       by a user. The interior of the lid 12 includes a centrally-located circular compartment 20 that is positionable at the opening 11 when the lid 12 is located thereat. Typically the compartment 20 is closed by an openable seal such as a foil or plastic membrane 21 which  
25       is affixed to the edge rim 22 of the compartment 20 by an appropriate sealant, such as an adhesive, or as a result of a welding process (ie. conductively or inductively welded).

The interior surface 17 of the skirt 16 of the lid 12 includes a threaded formation 13 which in use is mated to a  
30       threaded formation 15 located at the exterior surface of the opening throat 11 of the receptacle, to retain the lid thereat. The lid is fitted to or removed from the opening throat 11 by rotation to respectively couple or to decouple the mating threads 13, 15.

35       In use the compartment 20 contains a substance which is designated for mixing with a fluid which is located in

- 9 -

the receptacle. The seal 21 maintains a barrier to fluid communication between the substance and the fluid in the receptacle until such time as the device 10 is actuated and the seal 21 is broken, as will be described.

5 The device 10 also includes a projection in the form of a support flange 28 which is joined via a thin section hinge 30 to a hingedly moveable cutter 32 and associated deflection arm 34. In the preferred embodiment, the support flange 28, moveable cutter 32 and deflection arm 34  
10 are positioned on and are integral with the interior surface 36 of a circular cross-sectional sleeve 38 which is inserted into the receptacle throat opening 11.

The lid 12 also includes engagement means in the form of a longitudinal rib 24 which projects outwardly from the  
15 external wall 26 of the compartment 20. When assembled, there is at least a small clearance distance between the interior surface 36 of the sleeve 38 and the longitudinal rib 24, in order to allow relative movement therebetween. The longitudinal rib 24 on the compartment 20 external wall  
20 26 is arranged in use to interact with the deflection arm 34 so as to bias the cutter 32 into a position that opens the sealed compartment 20, as will be described.

In further embodiments, multiple longitudinal ribs or other protrusions of some kind can be arranged on the  
25 external wall of the compartment (for example, see Figures 16 and 17) to function as an engagement means.

The sleeve 38 also has a mounting in the form of a circumferential retaining rib 70 located on the internal wall 36 of the sleeve 38 and a groove 71 located on the  
30 external wall 26 of the compartment 20 in which the retaining rib 70 is received and seated in use. The retaining rib 70 is freely rotatable within said groove 71 in use so that the lid (and compartment) can be turned with respect to the sleeve 38 since there is a narrow annular  
35 clearance gap between the external wall 26 of the compartment 20 and the interior surface 36 of the sleeve

- 10 -

38. By seating the rib 70 in the said groove 71 on the external wall 26 of the compartment 20, the sleeve 38 is axially fixed in one location in relation to the compartment 20 and thus the lid 12. In further embodiments  
5 the mounting can be present in other forms, for example including a partial circumferential retaining rib.

The sleeve 38 also has a deformable retaining means in the form of a plurality of elongate flanges 72 located at the external wall 39 of the sleeve 38 and projecting  
10 outwardly therefrom. In the preferred embodiment shown, these elongate flanges 72 are arranged tangentially to the external wall 39 so as to provide a frangible, frictional interfit for retention of the sleeve 38 at the interior surface 25 of the throat 11, and to generally prevent the  
15 relative rotation of the sleeve 38 in the throat 11 whilst the cap 12 is being unscrewed from the throat 11, and whilst the compartment 20 is thus being rotated with respect to, and internally of, the sleeve 38. The recesses 29 located at the interior surface 25 of the throat 11 can  
20 also assist the interfit of the elongate flanges 72 with the throat 11 by partial receipt of those flanges 72.

In further embodiments, protrusions of different shapes and orientations other than the tangential elongate flanges 72 can be used. For example, dimples can be  
25 arranged on the external wall of the sleeve for receipt in shallow cavities positioned on the interior surface of the throat, as long as the sleeve is initially held in an associative frictional engagement with the throat of the receptacle. Since the association of the sleeve with the  
30 receptacle throat can vary somewhat depending upon the ambient temperature, or with the manufacturing tolerances of the various components, the use of protrusions on the external wall of the sleeve is preferred compared with the use of smooth-walled sleeves.

35 The sleeve 38 also has a rib flange 31 located at its interior surface 36 and which is arranged to abut the

- 11 -

longitudinal rib 24 at some point during rotatable movement of the lid 12 at the receptacle. The function of this rib flange 31 during unscrewing of the lid 12 from the throat 11 of the vessel will be described.

5           In other embodiments the support flange, moveable cutter and deflection arm can be arranged to be integrally formed at the interior surface of the opening of the receptacle, or even as part of a partial sleeve insertable in the receptacle mouth. In still other embodiments there  
10 can be more than one projection including the support flange, moveable cutter and deflection arm located at the receptacle or sleeve interior surface.

          The operation of the component parts of the device 10 in use will now be described. In the preferred embodiment,  
15 and as best shown in the series of Figures 5 to 8 which show the sequential position of the various parts of the device during use, a user grips and rotates the lid 12 in relation to the receptacle in a given direction G. The threaded formation 13 of the lid 12 is thus moved in the  
20 direction of disengagement from the threaded formation 15 at the throat 11 of the receptacle. As the lid 12 is rotated, it is moved relative to the receptacle and to the sleeve 38 associated with the receptacle, the sleeve 38 being mounted via the deformable elongate flanges 72 which  
25 frictionally engage the sleeve with the opening throat 11 of the receptacle. The rotation of the lid 12 with respect to the sleeve 38 is also guided by the motion of the circumferential retaining rib 70 of the sleeve 38 within the groove 71 located on the external wall 26 of the  
30 compartment 20 of the lid 12. The lid 12 is thus turned with respect to the sleeve 38 without axial displacement therebetween.

          During the rotational motion of the lid 12 in direction G, the longitudinal rib 24 located at the  
35 exterior of the compartment is moved in contact with the projecting deflection arm 34 of the sleeve. As rotation of

- 12 -

the lid 12 continues in direction G, the deflection arm 34 is hingedly moved in the direction of arrow Z (see sequential Figures 5 to 8 where the movement is clearly shown). This movement causes a likewise hinged deployment  
5 of the associated cutter 32 about hinge 30. The cutter 32 moves into contact with the openable seal 21 and breaks the seal 21 (see Figure 6). As the lid 12 is further rotated in the given direction G, the stationary cutter 32 is moved to further break or cut the seal at or near the edge rim 22  
10 of the compartment 20. At some point sufficient of the seal is cut, torn or detached to allow a substance held in the compartment 20 to pass into the adjoining receptacle, so that mixing can commence.

In further embodiments the projection can include  
15 parts other than a cutter, for example a piercing element such as a spike which can break the openable seal and allows a gaseous, liquid or powdered substance to flow from the compartment 20 into the adjoining receptacle such as a bottle or container. The actuation of the projection can  
20 be by one or more engagement ribs of different shapes or configurations than the rib 24 positioned on the compartment 20 in the preferred arrangement. In still further embodiments, the deflection of the cutter can occur by other than a hinging action, for example the engagement  
25 means can act on a trigger release associated with the projection to move at least a portion of the projection so as to open the seal.

When the openable seal is cut it is undesirable for the seal 21 to completely detach from the edge rim 22 of  
30 the compartment 20, especially if the receptacle contains foodstuffs or items for human use. To ensure that this does not occur, as the lid 12 and compartment 20 are rotated in the given direction G, the longitudinal rib 24 on the external wall 26 of the compartment eventually comes  
35 into abutment with the rib flange 31 which is located at the interior surface 36 of the sleeve 38, the sleeve 38

- 13 -

being, up to this point, stationary with respect to the receptacle. Once said abutment occurs, further rotational cutting of the seal 21 is prevented, as the abutment of the rib 24 and rib flange 31 prevents the further act of rotation of the lid 12 relative to the sleeve 38/receptacle as is best shown in Figure 8. A narrow bridge width 33 of seal material remains uncut, and thus the remainder of the seal 21 is retained at the compartment 20. At the point where sufficient of the seal 21 is cut, torn or detached to allow a substance held in the compartment 20 to pass into the adjoining receptacle, mixing of the substance and the receptacle contents can commence.

In the preferred embodiment of the device 10, the abutment of the rib 24 located on the external wall 26 of the compartment 20 and the rib flange 31 on the interior surface 36 of the sleeve 38 can also allow the sleeve 38 to be removed from its association with the receptacle. As the user applies an additional force to further rotate the lid in the direction G so that the longitudinal rib 24 pushes harder against the rib flange 31, this results in the lid 12 and the sleeve 38 rotating together but only as allowed by the deformation of the elongate flanges 72 which are frictionally engaged with the interior surface of the opening throat 11 of the receptacle. These flanges 72 bend sufficiently under the applied force from the user to thereby allow detachment of the sleeve 38 from its frictional association with the receptacle. At that point, the circumferential retaining rib 70 of the sleeve 38 which is located in the groove 71 on the external wall 26 of the compartment 20 of the lid 12, acts to prevent axial displacement of the sleeve 38 with respect to the compartment 20 of the lid 12, and so maintains the freed sleeve 38 in position with respect to the lid 12. Thus, advantageously, the user may then discard the lid 12 and sleeve 38 which includes the cutter 32, and consume fluid directly from the throat opening 11 of the receptacle

- 14 -

without either separately having to remove the sleeve 38/cutter 32 by hand, or risking injury to the lips or mouth of the user by drinking out of the receptacle fitted whilst with the cutter 32 at or adjacent the mouth thereof.

5 It is further noted that, in the preferred embodiment shown in the drawings, the length of each screw thread 13/15 used to engage the lid 12 at the throat opening 11 is calculated equivalent to the circumferential distance which the longitudinal rib 24 travels until its abutment with the  
10 rib flange 31 occurs. In other words, the lid and receptacle threads (respectively 13, 15) become disengaged at the same point at which the cutting of the seal 21 by the cutter 32 ceases, leaving an uncut narrow width bridge 33 of seal material 21.

15 When the lid 12 is initially attached to the opening of the receptacle, it is located thereon by rotation in a direction G' which is opposite to the aforementioned given direction G for unscrewing the lid 12 (which also causes an opening of the seal 21). Because of the initial angle of  
20 orientation of the deflection arm 34, when the lid 12 is moved in the direction G' it is not caused to deflect and thus to move the cutter 32 into a position of breaking the seal 21 (see Figure 5, for example). The movement of the deflection arm 34 over and past the longitudinal rib 24 in  
25 the direction G' is facilitated by a slight rounding of the trailing edge 41 of the deflection arm 34, as shown in the Figure 6c.

In further embodiments the lid need not be attached to the receptacle by a threadable coupling, but can simply be  
30 a 'bump on' lid which is snapped on, but which can still rotate to cause opening of the compartment in direction G.

In further embodiments shown in Figures 10 to 15, the compartment 20 in the lid can have a second opening to allow access thereinto, other than via the seal at the edge  
35 rim 22. Figures 10 to 12 show one such embodiment of the invention 52 where like parts shown in previous embodiments



- 15 -

have like numbers. In this embodiment, the lid 50 is arranged for additional access to the compartment 20 via a closeable orifice 48 in the circular top plate 14 of the lid 50. As shown in these Figures, a removeable or insertable disc 44 is arranged for engagement with a rim 46 of the orifice 48 when located in a closed position. The compartment 20 can thus be accessed from both within the receptacle to which the lid 50 is attached, and from outside the lid 50. In further embodiments the disc can be hinged to the rim 46 of the orifice 48 by, for example, a plastic hinge, so that it is not entirely removeable but simply frictionally fittable to the orifice 48.

Such an embodiment 52 is useful if a lid manufacturer wishes to provide a lid 50 already fitted with an openable seal in the form of a foil or plastic membrane 21. Thus the purchaser of lids 50 (for example the actual bottler/supplier of drinks or medicines etc) can insert the desired substance into the lid 50 compartment 20 via orifice 48 and replace/insert the disc 44 without needing to themselves go to the expense of developing, say, a foil membrane applicator or process for use once the substance has been placed in the compartment 20.

Once the lid 50 itself has been rotated in direction G to actuate the deployment of the cutter 32, and the mixing of the substance in the compartment with the fluid in the receptacle has been accomplished, a user of the combined fluid and substance can either remove the lid 50 entirely or restore the lid 50 to its tightened position by rotation in the direction G' and then remove (or hingedly open) the insertable disc 44 in order to be able to access the mixture via the narrower opening of orifice 48. The orifice 48 may be more useful to drink or dispense liquid out of in some situations, for example while the user is in motion and spillage is preferably minimised.

In a further embodiment of the invention 62 as shown in Figures 13 to 15, the lid 54 of the device can include

- 16 -

the feature of a closeable projecting teat in the form of a drink-through spout 56 similar to that known in water and sports-type drink bottles. Typically the spout 56 is positioned over the orifice 48 in the lid 54 (in the location where the lid disc 44 is located in the embodiment shown in Figure 10 to 12). The spout 56 also includes a retractable drink-through cap 58 which is fitted over the spout 56 and is slidably moveable from a closed position where the cap 58 is in close contact with the spout 56 (so as to prevent the flow of liquid from the compartment 20 via the discharge hole 60 in the spout 56) to an open position where the cap 58 is moved away from the spout 56 (so as to allow flow of liquid from the compartment 20 via the discharge hole 60 and through the corresponding hole 62 in the cap 58). In use the cap 58 can be pulled upwardly into an 'open' position so that fluid (or fluid-solid mixtures etc) can be dispensed from the receptacle. Closure of the spout 56 can be effected by depressing the cap 58. Prior to drinking the contents of the receptacle, the rotation of the cap 54 thereon can initiate the movement of the cutter 32 to break the seal on the compartment 20 and to release the substance from the compartment 20, as already described.

In any of the previously described embodiments the lid 12, 50, 54 can be fitted with a tamper-evident seal. Referring to the Figures, the seal is shown in the form of a strip 66 which is formed as a portion of the lid 12, 50, 54 and which is joined to the edge rim 64 of the lid 12, 50, 54 by a line of weakness (eg a series of perforations or a thin section of lid material). In use when the lid 12, 50, 54 is fitted to a receptacle in the form of a bottle or container, the strip 66 is in contact with the exterior surface of the receptacle. The innermost circumferential face of the strip 66 has a series of projecting teeth 68 or serrations which initially are in gripping contact with the receptacle. In use, before the

- 17 -

lid 12, 50, 54 can be rotated to cut the seal 21 at the edge rim 22 of the compartment 20, the tamper evident strip 66 needs to be physically torn off the rim 64 of the lid 12, 50, 54 so that the teeth 68 no longer grip onto the exterior surface of the receptacle. In further embodiments the tamper-evident strip may be laterally expanded during the rotational movement of the lid and the strip need not be completely torn from the lid. In such an example the relative movement of the lid and the resistance to movement of the strip, because of the grip of the teeth onto the exterior surface of the receptacle, can cause the partial separation of the strip from the lid.

A tamper-evident strip can provide a convenient visual indication to a potential user of the receptacle that the lid 12, 50, 54 has already been at least partially rotated, and, as such, it is likely that the seal 21 at the rim 22 of the compartment 20 has also been perforated or torn by that rotational movement. Thus the quality or integrity of the substance held in the compartment 20 may have been compromised. In an alternative arrangement, the receptacle can be at least partially transparent, so that a user can determine if the seal at the compartment 20 has already been compromised.

Figures 16 to 19 show an alternative embodiment of a lid 120 and sleeve 380 for location at an opening throat of a receptacle. In order to avoid repetition and for ease of reference, similar components and features of this alternative embodiment of the invention have been designated with an additional "0", such as the lid 120. The lid 120 has a plurality of engagement means in the form of longitudinal ribs 240 which projects outwardly from the external wall 260 of the compartment 200. When assembled, there is at least a small clearance distance between the interior surface 360 of the sleeve 380 and the longitudinal ribs 240, in order to allow relative movement therebetween. The longitudinal ribs 240 on the compartment 200 external

- 18 -

wall 260 are arranged in use to bias the cutter 320 into a position that opens the sealed compartment 200 in a similar manner as already described. The sleeve 380 has a smooth exterior surface which is manufactured to be of a tight frictional fit for receipt within the receptacle opening throat. In this arrangement, the rotational removal of the lid 120 from the receptacle causes compartment opening but does not facilitate detachment of the sleeve 380 from its association with the receptacle, and the sleeve 380 remains in position during pouring or consumption of the contents of the vessel from the opening throat.

The device can be used in many different applications, for example for pharmaceutical and drug dispensing, 'sports' type and vitamin supplement drinks and alcoholic and non-alcohol mixer drinks. The device can also be applied to the introduction of any chemicals into a process liquid, for example a process where a concentrate of some kind is required to be introduced into water or a base carrier, for example colouring and tinting (in hairdressing or graphic arts printing). In a further example, an industrial type application can be in the mixing of resins, glues and epoxy compounds, or other two-part products. The substance being dispensed from the compartment can be a liquid for example an ink or an emulsion, or solid materials such as powders or ground material, tablets, granules, chopped leaves or plant matter etc. The substance can be maintained in a sterile environment once it is sealed in the airtight and watertight compartment. The integrity of many products is enhanced when mixed or combined immediately prior to their use or consumption.

The operation of the device is intuitive, simply requiring the cap to be unscrewed from the receptacle (or in some cases merely turned in relation to the receptacle) in order to effect dispensation of the substance from the compartment. Because of its simplicity, the tooling costs for manufacturing such a device are minimised. In many of

- 19 -

the prior art devices, the tooling costs are expensive because the devices have too many components that require assembly, and by their shape and configuration limit the type of substances that can be dispensed.

5       The device may be of any particular shape, suitable for use in receptacle mouths of different shapes, for example round, oval, square etc as the situation demands. In further embodiments the compartment can be of any suitable shape that fits into the mouth of the receptacle,  
10       for example a circular, square or rectangular cylinder, and made of lightweight plastic, foil metal or other material which can be used to form a stable bladder or chamber that separates a substance from the fluid in the receptacle.

15       The materials of construction of the lid and the engagement means, the sleeve (if there is one) and the projection, can comprise any suitable materials which can be shaped, formed and fitted in the manner so described, such as metal or hard plastics which can be injection moulded to give a structurally sound device.

20       The embodiments of the invention shown can provide an improved two part vessel which can keep the contents of a compartment separated from the contents of the main portion of the vessel until mixing is required. By associating the projection with the receptacle (including, for example, a  
25       sleeve positioned in the mouth of the receptacle), and by causing the projection itself to be moved, the lid including the compartment can be of simpler construction than those known in the art for this purpose, and, as a consequence, simpler to use. Furthermore, as a result, the  
30       method of opening the receptacle is simplified in comparison to the known prior art devices so that the user only needs to undertake one intuitive action of turning the lid of the receptacle to accomplish the two separate functions of opening the compartment in the lid to allow  
35       combining of the contents of the compartment and the receptacle, and opening the receptacle itself, immediately

- 20 -

prior to use of the combined contents.

It is to be understood that, if any prior art information is referred to herein, such reference does not constitute an admission that the information forms a part  
5 of the common general knowledge in the art, in Australia or any other country.

Whilst the invention has been described with reference to a number of preferred embodiments it should be appreciated that the invention can be embodied in many  
10 other forms.

- 21 -

**CLAIMS**

1. A device for location at an opening to a receptacle comprising:

- 5       - a projection adapted for association with the receptacle at the opening;
- a lid for location at the opening including a compartment that is positionable at the opening when the lid is located thereat; and
- 10       - engagement means associated with the lid;
- wherein when the compartment is positioned at or near the opening and the lid is moved in a given direction relative to the receptacle, the engagement means is caused to act on the projection such that the
- 15       projection itself is moved into a position whereby it opens the compartment.

2. A device as claimed in claim 1 wherein the projection is hingedly moveable.

3. A device as claimed in claim 1 or claim 2 wherein the  
20       compartment is closeable in use with an openable seal.

4. A device as claimed in claim 3 wherein the projection least partially detaches the seal from the compartment.

5. A device as claimed in claim 4 wherein the projection includes a cutter portion adapted for cutting the seal.

25   6. A device as claimed in any one of the preceding claims wherein the engagement means is a protrusion located internally of the lid and externally of the compartment.

7. A device as claimed in claim 6 wherein the protrusion comprises at least one flange located on an external wall  
30       of the compartment and arranged to bias the projection into a location that opens the compartment as the lid is moved in the given direction.

8. A device as claimed in any one of the preceding claims wherein the lid is rotatable relative to the receptacle.

35   9. A device as claimed in claim 8 wherein the lid is

- 22 -

attached to the receptacle via rotation in a first direction and is detached via rotation in a second opposite direction, the second direction corresponding to said given direction.

5 10. A device as claimed in claim 8 or claim 9 wherein the lid is adapted for threadable engagement with the receptacle.

11. A device as claimed in any one of claims 3 to 5 wherein the compartment is also adapted for access from another  
10 location other than via the seal.

12. A device as claimed in claim 11 wherein the access adaptation is a closeable orifice in an exterior surface of the lid.

13. A device as claimed in claim 12 wherein a removeable or  
15 insertable disc is arrangeable for engagement with a rim of the orifice in a closed position.

14. A device as claimed in claim 11 wherein the access adaptation is a closeable projecting teat located at an exterior surface of the lid.

20 15. A device as claimed in any one of the preceding claims wherein the projection is integral with the receptacle at the opening or part of an insert locatable in the receptacle opening.

25 16. A device as claimed in claim 15 wherein the insert is a sleeve positionable in a neck of the receptacle and the projection protrudes inwardly of the sleeve.

17. A device as claimed in claim 16 wherein the sleeve comprises:

- a mounting for holding the sleeve in a freely  
30 rotatable but axially fixed manner in relation to the lid;
- one or more deformable retaining means located externally of the sleeve for holding it in an associative frictional engagement at the opening of  
35 the receptacle;



- 23 -

- a rib flange located at an internal wall of the sleeve and arranged to abut the engagement means upon rotatable movement of the lid at the receptacle,

5 wherein when the lid is rotated the engagement means abuts the rib flange and further rotation of the lid thus causes the lid and the sleeve to rotate together but only as allowed by the deformation of the retaining means, thereby detaching the sleeve from its  
10 association with the receptacle.

18. A device as claimed in claim 17 wherein the mounting comprises a circumferential or part-circumferential retaining rib located on the internal wall of the sleeve which in use is seated in a groove located on an outer  
15 surface of the compartment.

19. A device as claimed in any one of the preceding claims wherein the lid is provided with a tamper-evident seal.

20. A device as claimed in claim 19 wherein the seal is a strip detachably positioned at an edge rim of the lid  
20 which adjoins the receptacle in use.

21. A method of opening a compartment located in a lid positionable at a receptacle, including the step of moving the lid in a given direction relative to the receptacle at an opening of the receptacle so that a  
25 projection associated with the receptacle is itself moved into a position to open the compartment.

22. A method of opening a compartment located in a lid positionable at an opening of a receptacle wherein movement of the lid in a unidirectional rotation alone  
30 with respect to the receptacle causes compartment opening followed by removal of the lid from the receptacle.

23. A method as claimed in claim 22 wherein opening of the compartment brings it into fluid communication with the receptacle.

35 24. A method as claimed in any one of claims 21 to 23 that uses a device as defined in any one of claims 1 to 20.

- 24 -

25. A lid for location at an opening as defined in any one of claims 1 to 20.
26. A receptacle being fitted with a device as defined in any one of claims 1 to 20.
- 5 27. A sleeve which is insertable into an opening of a receptacle and having a projection as defined in any one of claims 1 to 20.

1/17




FIG. 1A




FIG. 1B




FIG. 1c

2/17










FIG. 2














8/17




FIG. 8B

FIG. 8A

9/17




FIG. 9B

FIG. 9A

10/17





FIG. 10

11/17

FIG. 11



12/17

FIG.12 B








FIG.12 A



14/17







16/17




FIG. 16




FIG. 17

17/17




FIG. 18




FIG. 19

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/01339

**A. CLASSIFICATION OF SUBJECT MATTER**Int. Cl. <sup>7</sup>: B65D 51/28, 41/50, 51/22

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI &amp; IPC - B65D 39/-, 25/-, 41/-, 47/-, 51/-, 55/-, A61J 1/-, 3/-, &amp; keywords (projection, cut, membrane, twist, engage, rib &amp; similar terms); Esp@ce &amp; EC -B65D 51/28B; USPTO &amp; similar terms &amp; USPTO and (unscrew, lid, compartment, jar, bottle)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5927549 A (WOOD) 27 July 1999 See abstract and drawings	1,3-5,8,10- 12,14,15,19- 21,24-27
X	WO 02/051711 A1 (VISY INDUSTRIAL PLASTICS LTD) 4 July 2002 See abstract and drawings	1-4,6- 13,15,19- 21,24-27
X	DE 19950884 A1 (WELLA AG) 26 April 2001 See abstract and drawings	21



Further documents are listed in the continuation of Box C



See patent family annex

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search  
27 November 2003Date of mailing of the international search report  
3 - DEC 2003

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE

PO BOX 200, WODEN ACT 2606, AUSTRALIA

E-mail address: pct@ipaustalia.gov.au

Facsimile No. (02) 6285 3929

Authorized officer

**STEPHEN CLARK**

Telephone No : (02) 6283 2781

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/01339

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 577200 B1 (LABORATORIOS CUSI, SA) 3 July 1996 See abstract and drawings (note claim 10 is an Inventive Step "X")	1,3-6,8- 12,14,15,19- 21,24-27
X	US 5246142 A (DIPALMA et al) 21 September 1993 See whole document, particularly drawings 10 and 14 (note claim 21 is an Inventive Step "X")	21-23
A	US 6138821 A (HSU) 31 October 2000 See drawing 8 in particular	1-27

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/01339

**Box I Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos :  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos :  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos :  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

**Box II Observations where unity of invention is lacking (Continuation of item 3 of first sheet)**

This International Searching Authority found multiple inventions in this international application, as follows:

Claims 1-21, 24 and 26 all relate to a device with a projection, a lid with an associated engagement means (except claim 21 which lacks the engagement means) and movement in a given direction causing the engagement means to act on the projection to open a compartment.

Claims 22-23 amount to unscrewing a lid to expose a compartment (claim 23 adding a further feature).

Claims 25 and 27 appear to define only portions of claims 1-120 rather than all of the features.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

**Remark on Protest**

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/AU03/01339

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report			Patent Family Member		
US	5927549	AU 31020/99	BR 9908924	CA 2321076	
		CZ 20003438	EP 1087894	WO 99/47428	
WO	02/051711	NONE			
DE	19950884	AU 11383/01	EP 1222122	WO 01/30665	
EP	577200	AU 41662/93	CA 2099744	ES 2064277	
		FI 933034	JP 6225924	US 5474209	
US	5246142	NONE			
US	6138821	AU 60667/99	BE 1013199	DE 19960238	
		FR 2802180	GB 2356844	IT TO991163	
		JP 2001261053	SE 9904722	SG 89307	
END OF ANNEX					